| TRANSMITTAL LETTER OT  | Attorney Docket No. 2001-1017  |  |  |  |  |
|--|--|--|--|--|--|
| DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371   |  | U.S. Application No. 10/04985                  |  |  |  |
| INTERNATIONAL APPLN. NO.   | INTERNATIONAL FILING DATE  |  |  |  |  |
| PCT/NL00/00574   | 17 AUGUST 2000   | 19 AUGUST 1999                                 |  |  |  |
| TITLE OF INVENTION: GREENHOUSE AS WELL AS ROOF ELEMENT FOR SUCH A GREENHOUSE HAVING INCREASED LIGHT TRANSMISSION   |  |  |  |  |  |
| APPLICANT(S) FOR DE/EO/US: JOHANNES ANDREAS STOFFERS AND PIETER JAN SONNEVELD  |  |  |  |  |  |
| Applicant herewith submits to the Unite  | ed States Designated Elected Office  | e (DO/EO/US) the following items and           |  |  |  |
| other information:   | itama concerning a filing under 25   | 118.0. 371                                     |  |  |  |
|  | items concerning a filing under 35   |  |  |  |  |
|  | QUENT submission of items conce  |  |  |  |  |
| The submission must include i  | pegin national examination procedu<br>tems (5), (6), (9) and (21) indicated  | d below.                                       |  |  |  |
| _4.   The US has been elected by the state of the state o | ne expiration of 19 months from the  | e priority date (Article 31).                  |  |  |  |
| 5. 🛛 A copy of the International App   | olication as filed (35 U.S.C. 371 (c)  | (2))   |  |  |  |
| a. 🛛 is attached hereto (require   | ed only if not communicated by the   | International Bureau)                          |  |  |  |
| b. ☐ has been communicated b   | by the International Bureau. See att   | tached PCT/IB/308.                             |  |  |  |
| c. is not required, as the app   | lication was filed in the United Stat  | es Receiving Office (RO/US).                   |  |  |  |
| 6 An English language translation  | on of the International Application a  | s filed (35 U.S.C. 371 (c)(2))                 |  |  |  |
| a. 🔲 is attached hereto.   |  |  |  |  |  |
| a. is attached hereto. b. has been previously subm   | nitted under 35 U.S.C. 154(d)(4).  |  |  |  |  |
| Amendments to the claims of  | the International Application under  | PCT Article 19 (35 U.S.C. 371 (c)(3))          |  |  |  |
|  | ired only if not communicated by th  | e International Bureau).                       |  |  |  |
| b. have been communicated  | The state of the s |  |  |  |  |
| L a mite   | The state of the s |  |  |  |  |
| d. have not been made and  | will not be made.  |  |  |  |  |
|  | on of the amendments to the claims   | s under PCT Article 19 (35 U.S.C. 371 (c)(3)). |  |  |  |
| 122 1  | nventor(s) (35 U.S.C. 371(c)(4)).  |  |  |  |  |
| 10. An English language translation under PCT Article 36 (35 U.S.  |  | nal Preliminary Examination Report             |  |  |  |
| Items 11 to 20 below concern do  | ocument(s) or information includ   | led:   |  |  |  |
| 11.  Information Disclosure Statem   | nent (IDS) w/PTO-1449 - ⊠ Copy   | of IDS citations                               |  |  |  |
| 12. Assignment Papers (cover she   | eet & document(s))   |  |  |  |  |
| 13. A FIRST Preliminary Amendm   |  |  |  |  |  |
| 14. A SECOND or SUBSEQUEN  | T Preliminary Amendment.   |  |  |  |  |
| 15. A substitute specification.  |  |  |  |  |  |
| 16. A change of power of attorney  |  |  |  |  |  |
| 17. A computer-readable form of  | the sequence listing in accordance   | with PCT Rule                                  |  |  |  |
|  | A second copy of the published international application under 35 U.S.C. 154(d)(4).  |  |  |  |  |
|  |  | tional application (35 U.S.C. 154(d)(4)).      |  |  |  |
|  |  | on Report (PCT/IPEA/409), International        |  |  |  |
| Search Report (PCT/ISA/210), Abstract on a separate sheet, Application Data Sheet  |  |  |  |  |  |
| ,  | 1  |  |  |  |  |

| U.S. APPLICATION   | 100054   | INTERNATIONAL APP<br>PCT/NL00/00574             | PLN. NO.                | ATTOR<br>2001-1 | RNEY DOCKET            | NO.    |
|--|--|---|-------------------------|-----------------|------------------------|--------|
|  |  | <u> </u>  |                         | 2001-1          | CALCUL                 | ATIONS |
|  | e following fees are s   |   |                         |                 | PTO US                 | E ONLY |
| BASIC NATIONAL   | FEE (37 CFR 1.492  | (a) (1)-(5):                                    |                         |                 |                        |        |
| international search   | of preliminary examir<br>of fee paid to USPTO<br>orepared by the EPC | nation fee nor<br>and international<br>) or JPO | \$104                   | 0.00            |                        |        |
| USPTO but Interna  | inary examination fe<br>tional Search Repor                          | e not paid to<br>t prepared by                  | \$890                   | .00             |                        |        |
| International prelim<br>USPTO but Interna  | inary examination fe<br>tional search fee pai                        | e not paid to id to USPTO                       | \$740                   | .00             |                        |        |
| but all claims did no  |  | f PCT Article 33 (1)-(4                         | )\$710                  | .00             |                        |        |
| International prelim   | inary examination fe   | ee paid to USPTO<br>Γ Article 33 (1)-(4)        | \$100                   | 00              |                        |        |
|  |  | ATE BASIC FEE AMO                               |                         |                 | \$ 890.00              |        |
| 1 : :  |  | oath or declaration th                          |                         |                 | \$ 130.00              |        |
| Months from the ea   | arliest claimed priorit  | y date (37 CFR 1.492(                           | e))                     |                 | -                      |        |
| GLÀIMS   | NUMBER FILED   | NUMBER EXTRA                                    | RATE                    |                 |                        |        |
| Total Claims   | 13 - 20 =  | 0   | X \$18.00               |                 | \$                     |        |
| Independent Claims   | 2 - 3 =  | 0   | X \$84.00               |                 | \$                     |        |
| MULTIPLE DEPEN   | ND CLAIM(S) (if appl   |   | + \$280.00              |                 | \$                     |        |
| ######################################   |  | TOTAL OF ABO                                    |                         |                 | \$ 1,020.00            |        |
| Applicant claimapove are reduced   | ns small entity status<br>by ½.                                      | See 37 CFR 1.27.                                | The fees indicate       | d<br>+          | \$                     |        |
| SUBTOTAL =   |  |   |                         | \$ 1,020.00     |                        |        |
| Processing fee of \$130.00 for furnishing the English translation later than \( \) 20 \( \) 30 months from the earliest claimed priority date (37 CFR 1.492Z(f)).  |  |   | _] 30                   | \$              |                        |        |
|  |  |   | AL NATIONAL F           |                 | \$ 1,020.00            |        |
| Fee for recording the enclosed assigned (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) \$40.00 per property +  |  |   | be<br>erty +            | \$              |                        |        |
|  |  | TOTAL   | FEES ENCLOSI            | ED -            | \$ 1,020.00            |        |
|  |  |   |                         |                 | Amount to be refunded: | \$     |
| j  |  |   |                         |                 | Charged:               | \$     |
| A Check in the amount of \$1,020.00 to cover all fees is attached.  The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to Deposit account No. 25-0120 in the name of Young & Thompson, as described below. A duplicate copy of this sheet is enclosed. |  |   |                         |                 |                        |        |
| The Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 25-0120 for any additional fee required under 37 C.F.R. §§ 1.16 or 1.17.   |  |   |                         |                 |                        |        |
| 745 South 23 <sup>rd</sup> Str<br>Arlington, VA 222<br>Telephone (703) 5   | .02<br>521-2297  |   | SIGNATURE Benoit Castel | /sen            | oit Cast               |        |
| Y&T Customer No  | 0. 000466  | 00466   | NAME                    |                 |                        |        |
| BC/lmt<br>Date: February 1   |  | ENT_TRADEMARK OFFICE                            | 35,041<br>REGISTRATION  | N NO.           |                        |        |

PATENT 2001-1017

#### IN THE U.S. PATENT AND TRADEMARK OFFICE

In re application of: Johannes Andreas STOFFERS etal.

Appl. No.:

NEW

Group:

Filed:

February 19, 2002 Examiner:

For:

GREENHOUSE AS WELL AS ROOF ELEMENT

FOR SUCH A GREENHOUSE HAVING INCREASED

LIGHT TRANSMISSION

#### PRELIMINARY AMENDMENT

Assistant Commissioner for Patents Washington, DC 20231

February 19, 2002

Sir:

The following preliminary amendments and remarks are respectfully submitted in connection with the above-identified application.

#### IN THE ABSTRACT OF THE DISCLOSURE:

Please add the Abstract of the Disclosure attached on a separate sheet attached hereto.

#### IN THE CLAIMS:

Please amend the claims as follows:

--4. (amended) Greenhouse (1, 28) according to claim 1, characterised in that the roof surfaces (52, 53, 54, 55) are of doubled-wall construction, having a base sheet (51, 73, 74) and

transverse links (58, 59, 75, 76, 77) between the points of the apexes and/or the base edges (60, 61, 62, 63, 78, 79) of the roof surfaces and the base sheet.—

- --5. (amended) Greenhouse (1, 28) according to Claim 3, characterised in that a distance ( $d_2$ ,  $d_3$ ,  $d_4$ ) between the base edges (18, 19, 20, 21, 78, 79) of the pairs of second roof surfaces (12, 13, 14, 15, 71, 72) is between 0.5 and 0.001 times the distance ( $d_1$ ) between the base edges(11, 11', 11") of the pairs of first roof surfaces (5, 6, 7, 8).--
- --6. (amended) Greenhouse (1, 28) according to Claim 3, characterized in that a perpendicular distance ( $h_2$ ,  $h_5$ ) between the edge at the apex (16, 17, 27, 28) and the base edges (18, 19, 20, 21,60, 61, 62, 63) of the pairs of second roof surfaces is between 0.5 and 0.001 times the perpendicular distance between the edge at the apex (9, 10) and the base edges (11, 11', 11") of the pairs of the first roof surfaces (5, 6, 7, 8).--
- --9. (amended) Roof element (50, 80) according to Claim 7, characterized in that a distance between the base sheet (51, 81) and the apex (56, 57, 90) is between 1cm and 10cm, preferably between 1.5cm and 3cm.--
- --10. (amended) Roof between (50, 80)according to Claim 7, , characterized in that the distance (d<sub>3</sub>, d<sub>4</sub>) between the base edges is between 1cm and 10cm, preferably between 1.5cm and 3cm.-

- --11. (amended) Roof element (50, 80) according to Claim 7, characterized in that the angle ( $\theta$ ) of the roof surfaces is beteen 30° and 75°, preferably between 45° and 75°.--
- --12. (amended) Roof element (50, 80) according to Claim 7, characterized in that the roof element consists of one piece and is made from transparent plastic having a wall thickness of between 0.5mm and 5mm, preferably between 0.5mm and 2mm.--
- --13. (amended) Roof element (76, 77) according to Claim 7, characterized in that the roof element is provided with coupling means (78, 79) for joining to a similar roof element.--

#### REMARKS

Claims 1-13 are pending in the present application.

Entry of the above amendments is earnestly solicited. An early and favorable first action on the merits is earnestly requested.

Should there be any matters that need to be resolved in the present application, the Examiner is respectfully requested to contact the undersigned at the telephone number listed below.

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached page is captioned "VERSION WITH MARKINGS TO SHOW CHANGES MADE."

The Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any

overpayment to Deposit Account No. 25-0120 for any additional fees required under 37 C.F.R. § 1.16 or under 37 C.F.R. § 1.17.

Respectfully submitted,

YOUNG & THOMPSON

Benoît Castel, Reg. No. 35,041 745 South 23<sup>rd</sup> Street

Benoît Castel

745 South 23<sup>rd</sup> Street Arlington, VA 22202 Telephone (703) 521-2297

BC/lmt
Attachments

#### ABSTRACT OF THE DISCLOSURE

Greenhouse (1) provided with a roof element (2) having a multiplicity of transverse ribs (12, 13, 14, 15) or pyramids uniformly distributed over the roof element. The roof element can be constructed double-walled as a hollow-core sheet from transparent plastic and can comprise a base sheet with the rib-shaped or pyramid-shaped roof surfaces fixed thereon. The light yield in a horticultural greenhouse can be increased by the roof elements.

#### VERSION WITH MARKINGS TO SHOW CHANGES MADE

#### IN THE CLAIMS:

The claims have been amended as follows:

- --4. (amended) Greenhouse (1, 28) according to one of the preceding claims, claim 1, characterised in that the roof surfaces (52, 53, 54, 55) are of doubled-wall construction, having a base sheet (51, 73, 74) and transverse links (58, 59, 75, 76, 77) between the points of the apexes and/or the base edges (60, 61, 62, 63, 78, 79) of the roof surfaces and the base sheet.--
- --5. (amended) Greenhouse (1, 28) according to Claim 3-er 4, characterised in that a distance ( $d_2$ ,  $d_3$ ,  $d_4$ ) between the base edges (18, 19, 20, 21, 78, 79) of the pairs of second roof surfaces (12, 13, 14, 15, 71, 72) is between 0.5 and 0.001 times the distance ( $d_1$ ) between the base edges(11, 11', 11") of the pairs of first roof surfaces (5, 6, 7, 8).--
- --6. (amended) Greenhouse (1, 28) according to Claim 3,4 or 5, characterized in that a perpendicular distance ( $h_2$ ,  $h_5$ ) between the edge at the apex (16, 17, 27, 28) and the base edges (18, 19, 20, 21,60, 61, 62, 63) of the pairs of second roof surfaces is between 0.5 and 0.001 times the perpendicular distance between the edge at the apex (9, 10) and the base edges (11, 11', 11") of the pairs of the first roof surfaces (5, 6, 7, 8).--
- --9. (amended) Roof element (50, 80) according to Claim 7 or 8, characterized in that a distance between the base sheet

- (51, 81) and the apex (56, 57, 90) is between 1cm and 10cm, preferably between 1.5cm and 3cm.--
- --10. (amended) Roof between (50, 80)according to Claim 7,  $\frac{8 \text{ or } 9}{3}$ , characterized in that the distance (d<sub>3</sub>, d<sub>4</sub>) between the base edges is between 1cm and 10cm, preferably between 1.5cm and 3cm.--
- --11. (amended) Roof element (50, 80) according to Claim 7,8-or 9, characterized in that the angle ( $\theta$ ) of the roof surfaces is beteen 30° and 75°, preferably between 45° and 75°.--
- --12. (amended) Roof element (50, 80) according to one of Claims 7 to 11, Claim 7, characterized in that the roof element consists of one piece and is made from transparent plastic having a wall thickness of between 0.5mm and 5mm, preferably between 0.5mm and 2mm.--
- --13. (amended) Roof element (76, 77) according to one of Claims 7 to 12, Claim 7, characterized in that the roof element is provided with coupling means (78, 79) for joining to a similar roof element.--

Greenhouse as well as roof element for such a greenhouse having increased light transmission

The invention relates to a greenhouse having a transparent roof construction with a longitudinal direction and a transverse direction located perpendicularly thereto, having various pairs of first roof surfaces in succession in the transverse direction, the first roof surfaces of a predetermined pair running at an angle with respect to a horizontal from a base edge oriented in the longitudinal direction of the greenhouse to a common apex. The invention also relates to a roof element for use in such a greenhouse.

It is known from the publication entitled "Second International Symposium on Models for Plant Growth", Environmental Control and Farm Management in Protected Cultivation, number 456, March 1998, to provide horticultural greenhouses with roof surfaces in succession in the transverse direction which run in the shape of a point towards an apex. For angles to the horizontal of greater than 45° the light transmission for radiation which is incident perpendicularly on the greenhouse is found to increase substantially. This is particularly important in horticultural greenhouses since one per cent more light yield results in approximately one per cent more yield of crops.

An aim of the present invention is to provide a roof construction of the abovementioned type, provided with a quantity of pairs of roof surfaces which are laid in contact with one another and come together in an apex, the light transmission being increased.

To this end the roof construction according to the present invention is characterised in that the greenhouse is also provided with pairs of successive second roof surfaces in the longitudinal direction, which second roof surfaces run at an angle with respect to the horizontal from a base edge oriented in the transverse direction of the greenhouse to a common apex.

It has been found that a zigzag or ribbed pattern of the roof surfaces extending in two perpendicular directions is able to increase the light yield by 10%-20% compared with roof constructions which are of zigzag construction only in the transverse direction. In a first embodiment the pairs of roof surfaces form pyramids which are joined to one another along their sides to give a continuous roof construction.

In another embodiment of a greenhouse according to the invention the pairs of first roof surfaces are in contact with one another along edges at the apex, wherein base edges and the edges at the apex of the pairs of first roof surfaces extend parallel to one another in

5

10

15

20

25

30

30

5

10

WO 01/13704 PCT/NL00/00574

2

the longitudinal direction, wherein the pairs of second roof surfaces are in contact with one another along edges at the apex and wherein the base edges and the edges at the apex of the second pairs of roof surfaces extend parallel to one another from a base edge of a first roof surface to the edge at the apex of the first roof surface concerned. By this means successive transverse ribs are formed in the longitudinal direction of the greenhouse.

It is preferable to construct roof elements with a zigzag pattern double-walled as a hollow-core sheet so that, on the one hand, adequate strength and insulating effect of the roof construction is obtained whilst, on the other hand, the light transmission is increased. The double-walled roof elements comprise a base surface made of, for example, polycarbonate with a thickness of 0.8 mm on which a zigzag-shaped sheet with ribs approximately 20 mm high is fixed. Preferably, the double-walled roof element is made in one piece. The roof elements can be of modular construction and are provided with coupling means for joining to similar roof elements.

A greenhouse according to the present invention and a roof element will be explained in more detail below with reference to the appended drawing. In the drawing:

Figure 1 shows a diagrammatic, perspective view of a roof with a roof construction that is in zigzag form in the transverse direction and the longitudinal direction,

Figure 2 shows a diagrammatic, perspective view of a roof construction formed from a series of pyramids,

Figure 3 shows a cross-section of a double-walled roof element in the form of a hollow-core sheet according to the present invention,

Figure 4 shows an alternative embodiment of a double-walled roof element in the form of a hollow-core sheet according to the invention,

Figure 5 shows a double-walled roof element formed by a series of pyramids, and

Figure 6 shows two roof elements joined to one another by means of coupling means.

Figure 1 shows a greenhouse 1, such as, for example, a greenhouse of the Venlo type having a transparent roof construction 2. The roof construction 2 is supported on uprights 3 and horizontal lattice girders 4, which are shown here diagrammatically only. The height a of a greenhouse as shown in Figure 1 is, for example, 4 m, whilst the width,  $d_1$  in the transverse direction D, is 8 m for a length in the longitudinal direction L of, for example, 100 m. The roof construction 2 comprises pairs of first roof surfaces 5, 6; 7, 8, which run from a base edge 11, 11', 11" at an angle  $\theta$  of approximately 20° with respect to the horizontal and which are fixed to one another along a respective apex 9, 10. The height  $h_1$ 

10

15

20

25

30

of the apex 9, 10 above the lattice girder 4 is, for example, 1.45 m. In the longitudinal direction L the pairs of roof surfaces 5, 6; 7, 8 are provided with transverse ribs, formed by pairs of second roof surfaces 12, 13; 14, 15. The roof surfaces 12, 13; 14, 15 run at an angle γ from base edges 18. 19; 20, 21 and are joined to one another along edges at the apex 16, 17. The distance d₂ between the base edges 18, 19; 20, 21 of the pairs of second roof surfaces 12, 13; 14, 15 is, for example, 2 cm, whilst the height h₂ of the edge at the apex 16, 17 above the plane of the base edges 18, 19; 20, 21 is 1.7 cm. As a result of fitting the pairs of zigzag-shaped second roof surfaces 12, 13; 14, 15 the light yield is increased by approximately 10% for a single layer roof construction and by approximately 20% for a double layer roof construction as is shown in Figure 3 and Figure 4, compared with known greenhouses where only pairs of first roof surfaces 5, 6; 7, 8 are present.

Figure 2 shows an embodiment of a greenhouse 28 having a roof construction 29 in which the base edges 30, 31, 32, 33 of pairs of first roof surfaces 34, 35 and pairs of second roof surfaces 36, 37 delimit rectangles in contact with one another, above which the roof surfaces 34, 35; 36, 37 come together in an apex 38, so that a multiplicity of pyramids 39, 40 is formed to increase the light yield. Here the length of the base edges 31, 32 is approximately 1 m, whilst the height of the pyramids is 1.7 m.

Figure 3 shows an embodiment of a double-walled roof element 50 in the form of a hollow-core sheet having a base sheet 51 and pairs of roof surfaces 52, 53, 54, 55 which are joined to one another along edges at the apex 56, 57 extending perpendicularly to the plane of the drawing. The base edges 60, 61, 62, 63 are joined via partitions 58, 59 to the base sheet 1. The thickness b<sub>1</sub> of the base sheet is, for example, 0.8 mm, the thickness b<sub>2</sub> of the surfaces 52, 53, 54, 55 is, for example, 1 mm, the height h<sub>3</sub> is, for example, 28 mm, whilst the distance d<sub>3</sub> between the base edges 60, 61, 62, 65 is, for example, 16 mm. The height h<sub>5</sub> is 13.9 mm.

The angle  $\theta$  of the roof surfaces 52, 53, 54, 55 to the horizontal is 60°. The material of the double-walled roof element 50 is, for example, polycarbonate, but this element can also be made from any other suitable transparent plastic.

Figure 4 shows an alternative embodiment of a double-walled roof element 70 having roof surfaces 71, 72, which are positioned at an angle, and base surfaces 73, 74, which are likewise positioned at an angle and which are joined to one another by partitions 75, 76, 77. The thickness  $b_3$  of the roof surfaces 71, 72 is, for example, 1 mm, the distance  $b_4$  between the roof surfaces 71, 72 and the base surfaces 73, 74 is, for example, 20 mm and

10

WO 01/13704 PCT/NL00/00574

4

the thickness  $b_4$  of the partition 77 is, for example, 0.8 mm. The distance  $d_4$  between the base edges 78, 79 is, for example, 30 mm.

Figure 5 shows an embodiment of a roof element 80 made from one piece of transparent plastic and having a base sheet 81. Four surfaces 82, 83, 84, 85 extend along four base edges 86, 87, 88, 89 of the base sheet 81 to a common apex 90. In this way a multiplicity of pyramids uniformly distributed over the base sheet 81 are formed. Here the length of the base edges 86, 87, 88, 89 is, for example, 1.5 m and the distance from the apex 90 to the base sheet 81 is 2.6 m.

Finally, Figure 6 shows two roof elements 90, 91 which are joined to one another via complementary fixing means 92, 93 which engage in a simple manner and in modular fashion form a roof construction according to the present invention.

10

15

20

25

30

يقدا

T.

#### Claims

- 1. Greenhouse (1,28) comprising a transparent roof construction (2,29) with a longitudinal direction (L) and a transverse direction (D) located perpendicularly thereto, having various pairs of first roof surfaces (5,6,7,8,36,37) in succession in the transverse direction (D), the first roof surfaces of a predetermined pair running at an angle ( $\theta$ ) with respect to a horizontal from a base edge (11,11',11",30,33) oriented in the longitudinal direction (L) of the greenhouse to a common apex (9,10,38), characterised in that the greenhouse is provided with pairs of successive second roof surfaces (12,13,14,15;34,35) in the longitudinal direction (L), which second roof surfaces extend at an angle ( $\gamma$ ) with respect to the horizontal from a base edge (18,19,20,21;31,32) oriented in the transverse direction (D) of the greenhouse to a common apex (16,17;38).
- 2. Greenhouse (28) according to Claim 1, characterised in that four mutually adjoining perpendicular base edges (30,31,32,33) each time delimit a rectangle, wherein the rectangles extend successively in the longitudinal direction (L) and the transverse direction (D) of the roof construction and wherein, for each rectangle, first and second pairs of roof surfaces (34,35,36,37) extend from the base edges (30,31,32,33) to a common apex (38) located above the rectangle concerned.
- 3. Greenhouse (1) according to Claim 1, characterised in that the pairs of first roof surfaces (5,6,7,8) are in contact with one another along edges at the apex (9,10), wherein the base edges (11,11',11") and the edges at the apex (9,10) of the pairs of first roof surfaces (5,6,7,8) extend parallel to one another in the longitudinal direction (L), wherein the pairs of second roof surfaces (12,13,14,15) are in contact with one another along edges at the apex (16,17) and wherein the base edges (18,19,20,21) and the edges at the apex (16,17) of the second pairs of roof surfaces (12,13,14,15) extend parallel to one another from a base edge (11,11',11") of a first roof surface (5,6,7,8) to the edge at the apex (9,10) of the first roof surface concerned.
- 4. Greenhouse (1,28) according to one of the preceding claims, characterised in that the roof surfaces (52,53,54,55) are of double-walled construction, having a base sheet (51,73,74) and transverse links (58,59,75,76,77) between the points of the apexes and/or

10

15

20

25

30

- 5. Greenhouse (1,28) according to Claim 3 or 4, characterised in that a distance  $(d_2,d_3,d_4)$  between the base edges (18,19,20,21,78,79) of the pairs of second roof surfaces (12,13,14,15,71,72) is between 0.5 and 0.001 times the distance  $(d_1)$  between the base edges (11,11',11'') of the pairs of first roof surfaces (5,6,7,8).
- 6. Greenhouse (1,28) according to Claim 3, 4 or 5, characterised in that a perpendicular distance  $(h_2,h_5)$  between the edge at the apex (16,17,27,28) and the base edges (18,19,20,21,60,61,62,63) of the pairs of second roof surfaces is between 0.5 and 0.001 times the perpendicular distance between the edge at the apex (9,10) and the base edges (11,11',11'') of the pairs of first roof surfaces (5,6,7,8).
- 7. Roof element (50,80) for use in a greenhouse, provided with various pairs of roof surfaces (52,53,54,55,82,83) in succession in a transverse direction (D) and a base sheet (51,81), wherein the roof surfaces of a predetermined pair run at an angle ( $\theta$ ) with respect to the base sheet from a base edge (60,61,62,63,86,88) oriented in a longitudinal direction (L) to a common apex (56,57,90), which roof surfaces (52,53,54, 55,82,83) are joined to the base sheet along the base edges and/or at the location of the apex.
- 8. Roof element (80) according to Claim 7, characterised in that the roof element is furthermore provided with pairs of second roof surfaces (84,85) in succession in a longitudinal direction (L) which run at an angle with respect to the base sheet (81) from a base edge (87,89) oriented in a transverse direction (D) to a common apex (90), wherein four base edges (86,87,88,89) perpendicular to one another always delimit a rectangle, wherein the rectangles extend successively in the longitudinal direction (L) and the transverse direction (D) of the base sheet (81) and wherein, for each rectangle, first and second pairs of roof surfaces (82,83,84,85) extend from the base edges (86,87,88,89) to a common apex (90) located above the rectangle concerned.
- 9. Roof element (50,80) according to Claim 7 or 8, characterised in that a distance between the base sheet (51,81) and the apex (56,57,90) is between 1 cm and 10 cm, preferably between 1.5 cm and 3 cm.

5

10

- 10. Roof element (50,80) according to Claim 7, 8 or 9, characterised in that the distance  $(d_3,d_4)$  between the base edges is between 1 cm and 10 cm, preferably between 1.5 cm and 3 cm.
- 11. Roof element (50,80) according to Claim 7, 8 or 9, characterised in that the angle ( $\theta$ ) of the roof surfaces is between 30° and 75°, preferably between 45° and 75°.
- 12. Roof element (50,80) according to one of Claims 7 to 11, characterised in that the roof element consists of one piece and is made from transparent plastic having a wall thickness of between 0.5 mm and 5 mm, preferably between 0.5 mm and 2 mm.
- 13. Roof element (76,77) according to one of Claims 7 to 12, characterised in that the roof element is provided with coupling means (78,79) for joining to a similar roof element.

#### (19) World Intellectual Property Organization International Bureau



## 

#### (43) International Publication Date 1 March 2001 (01.03.2001)

#### **PCT**

## (10) International Publication Number WO 01/13704 A1

(51) International Patent Classification<sup>7</sup>:

\_ \_

- (21) International Application Number: PCT/NL00/00574
- (22) International Filing Date: 17 August 2000 (17.08.2000)
- (25) Filing Language:

Dutch

(26) Publication Language:

English

A01G 9/14

(30) Priority Data: 1012866

19 August 1999 (19.08.1999) NL

- (71) Applicant (for all designated States except US): INSTITUUT VOOR MILIEU-EN AGRITECHNIEK (IMAGDLO) [NL/NL]; P.O. Box 43, NL-6700 AA Wageningen (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): STOFFERS, Johannes, Andreas [NL/NL]; Nic. Beetsstraat 15, NL-4041 XH Kesteren (NL). SONNEVELD, Pieter, Jan [NL/NL]; Van Schermbeeklaan 8, NL-7603 GJ Wageningen (NL).


- (74) Agent: JORRITSMA, Ruurd; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### Published:

With international search report.

[Continued on next page]

(54) Title: GREENHOUSE AS WELL AS ROOF ELEMENT FOR SUCH A GREENHOUSE HAVING INCREASED LIGHT TRANSMISSION




5 H Hyp, make


þ.


0 01/13704

(57) Abstract: The invention relates to a greenhouse (1) provided with a roof element (2) having a multiplicity of transverse ribs (12, 13, 14, 15) or pyramids uniformly distributed over the roof element. The roof element can be constructed double-walled as a hollow-core sheet from transparent plastic and can comprise a base sheet with the rib-shaped or pyramid-shaped roof surfaces fixed thereon. The light yield in a horticultural greenhouse can be increased by means of the roof elements according to the present invention.

PCT/NL00/00574







3/3

Fig 5





Fig 6



4.676

### COMBINED DECLARATION AND POWER OF ATTORNEY

(ORIGINAL DESIGN, NATIONAL STAGE OF PCT OR CIP APPLICATION)

As a below named inventor, I hereby declare that

My residence, post office address and citizenship are as stated below next to my name, I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

# Greenhouse as well as roof element for such a greenhouse having increased light transmission

the specification of which: (complete (a), (b) or (c) for type of application)

|          | REGULAR OR DES  | SIGN APPLICATION                  |  |  |  |
|----------|---|-----------------------------------|--|--|--|
| E a. [ ] | is attached hereto.<br>was filed on<br>Serial No.<br>(if applicable)                              | as Application and was amended on |  |  |  |
|          | PCT FILED APPLICATION ENTERING NATIONAL STAGE   |                                   |  |  |  |
| c. [X]   | was described and claimed in International application No. PCT/NL00/00574 filed on 17 August 2000 |                                   |  |  |  |
|          | and as amended on   | (if any)                          |  |  |  |

#### ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, paragraph 1.56(a).

In compliance with this duty there is attached an information disclosure statement 37 CFR 1.97

#### **PRIORITY CLAIM**

I hereby claim foreign priority benefits under Title 35. United States Code paragraph 119 of any foreign application (s) for patent of inventor's certificate listed below and have also identified below any foreign application for patent of inventor's certificate having a filing date before that of the application on which priority is claimed.

d. [ ] no such applications have been filed

e. [X] such applications have been filed as follows

# EARLIEST FOREIGN APPLICATION(S), IF ANY FILED WITHIN 12 MONTHS (6 MONTHS FOR DESIGN) PRIOR TO SAID APPLICATION

| Country         | Application<br>Number | Date of filing<br>(day, month, year) | Date of Issue<br>(day, month, year) | Priority claimed |
|-----------------|-----------------------|--------------------------------------|-------------------------------------|------------------|
| the Netherlands | 1012866               | 19 August 1999                       |                                     | Yes              |
|                 |                       |                                      |                                     |                  |
|                 |                       |                                      |                                     |                  |

| ļ.d           | ALL FOREIGN APPLICATION(S), IF ANY FILED MORE THAN 12 MONTHS  |                 |
|---------------|---|-----------------|
| (* 22<br>5 22 | (6 MONTHS FOR DESIGN) PRIOR TO SAID APPLICATION   |                 |
| 5 Act         | (6 MONTHS FOR DESIGN) PRIOR TO SAID APPLICATION  CONTINUES TION IN PART   |                 |
| ===<br>===    |   |                 |
| H             | *i={<br>^fr   |                 |
| P             |   |                 |
| = 1           | CONTINUATION-IN-PART  |                 |
| ê<br>Sant.    |   |                 |
| )=:<br>17.    | (Complete this part only if this is a continuation-in-part application)   |                 |
|               | (Complete this part only if this is a continuation-in-part application)   |                 |
| mgr.          |   | ation(s) listed |
| =             | below and, insofar as the subject matter of each of the claim of this application is not disclosed in the prior       |                 |
|               | application in the manner provided by the first paragraph of Title 35, United States Code, paragraph 112, I acknowled |                 |
|               | disclose material information as defined in Title 37, Code of Federal Regulations, paragraph 1.56(a) which occurred   | between the     |
|               | filing date of the prior application and the national or PCT international filing date of this application:           |                 |
|               | (Application Serial No.) (Filing date) (Status) (patented, pending, ab  | andoned)        |
|               |   |                 |
|               | (Application Serial No.) (Filing date) (Status) (patented, pending, about   | andoned)        |
|               | (Application Serial No.) (Filing date) (Status) (patented, pending, at  | a, ao no a      |

#### **POWER OF ATTORNEY**

As a named inventor, I hereby appoint the following attorney(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: Robert J. PATCH, Reg. No. 17,355, Andrew J. PATCH, Reg. No. 32,925, Robert F. HARGEST, Reg. No. 25,590, Benoît CASTEL, Reg. No. 35,041, Eric Jensen, Reg. No. 37,855, and Thomas W. PERKINS, Reg. No. 33,027 and Roland E. Long, Jr. Reg. No. 41,949 c/o YOUNG & THOMPSON, Second Floor, 745 South 23rd Street, Arlington, Virginia 22202.

Address all telephone calls to Young & Thompson at 703/521-2297.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that wilful false statements and the like so made are punishable by fine or imprisonment, or both under Section 1001 of Title 18 of the United States Code and that such wilful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor: STOFFERS, Johannes Andreas Inventor's signature

Date 9 - 2 - 2002

Country of Citizenship: the Netherlands NLX

Residence: KESTEREN, the Netherlands

Post Office Address: Nic. Beetsstraat 15, NL-4041 XH KESTEREN, the Netherlands

2-00

Full name of second inventor: SONNEVELD, Pieter Jan

Inventor's signature

Date 8-2-2002

Country of Citizenship: the Netherlands NLX

Residence: Wageningen, the Netherlands

Post Office Address: Van Schermbeeklaan 8, NL-7603 GJ WAGENINGEN, the Netherlands

CHECK PROPER BOX(ES) FOR ANY ADDED PAGE(S) FORMING A PART OF THIS DECLARATION